

Overview

Stainless steel nozzles with 4 front jets. Available upon request with carbide inserts.



Characteristics

APPLICATIONS

- penetration through occlusion of soap, grease, stones
- preliminary cleaning jobs before using chain rotating nozzle for roots removal
- reverse cleaning jobs (from house to main sewer)




ADVANTAGES

- sharp chisel shape improves breaking performance

Technical Specifications

Inlet	1/4" F	3/8" F	1/2" F	3/4" F	1" F	1" 1/4 F
Ø x L (mm)	19 x 30	25 x 40	38 x 55	52 x 85	69 x 115	78 x 142
Weight (kg)	26 gr	80 gr	240 gr	690 gr	1,57 kg	2,60 kg
Front Inserts	-	3 x 15° + 1 M4	3 x 15° + 1 M6 C	3 x 20° + 1 TE M6 C	3 x 20° + 1 TE M6 C	3 x 20° + 1 TE M10 C
Rear Inserts	-	6 x 20° drilled	6 x 20° M6 C	6 x 20° TE M6 C	6 x 20° TE M10 C	6 x 20° TE M6 C
Maximum Pressure (bar)	300	300	300	300	300	300
Flow (lt/min)	35-80	35-90	70-170	85-240	100-300	150-500
Working DN (mm)	30-100	30-100	50-250	80-300	150-400	150-500

Items

	Part Number	Description
	5560.08	3/8" F RAUT NOZZLE SS DRILLED
	5560.20	3/4" F RAUT NOZZLE SS with ceramic inserts
	5560.40	1" 1/4 F RAUT NOZZLE SS with ceramic inserts

GALLERY IMAGES

